

less'n'more

Athene Recessed Light A-MDL1

Dimmbarkeit

- integrated Pushbutton dimmer
- on site dimmable with a trailing edge dimmer

Oberfläche

- aluminum
- black
- white

flexible arm

- textile blue
- textile anthracite
- aluminum
- textile green
- textile red
- textile brown
- textile white
- textile black

Description

The Less'n'more Athene Recessed Light A-AL1 can be installed into a table. This lamp is also suitable for installation into a wall or ceiling. **An external transformer is supplied, which can only be mounted from behind outside the mounting plate**. This Athene recessed lamp has a flexible lamp arm that can be stretched and bent as required. At maximum extension of the lamp arm, the lamp has a height or length of 23 cm. The flexible lamp arm is available in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

The lamp head and the mounting plate or the lamp base are made of aluminum. The mounting plate has a diameter of 6 cm. Lamp head and mounting plate are offered in the surfaces aluminum and black. The beam angle of the light can be continuously adjusted between 25 and 100 degrees by turning the glass lens out of or into the lamp head. With a larger beam angle, the light is distributed over a larger area.

The Athene Recessed Light A-AL1 is operated with an integrated LED. The LED has a colour temperature of 2,700 Kelvin extra warm white. The table lamp is available dimmable on site with a trailing edge phase dimmer or with an integrated push button dimmer on the mounting plate. The version with push button dimmer can be switched and dimmed via the push button. The flexible lamp arm is offered in other colours on request. In addition to this recessed lamp, a larger lamp with a maximum height of 54 cm is also offered by Less'n'more.

Technical details

Country of Manufacture

Manufacturer

less'n'more

Designer

less'n'more

protection Scope of delivery

voltage suitability230 - 240 Voltmaterialaluminum, glassbeam angle25 - 100 degrees

IP43

LED

Wattage 4.8 W
LED inclusive
Colour Rendering Index 90
Luminous flux in Im 600

Color temperature in Kelvin 2,700 extra warm white

lamp stand dimensions 6 cm
light head dimensions 7 cm
bulb exchange on site itself
Dimensions H max. 23 cm