

Byok

Assiale L




Dimmbarkeit

- DALI regulable
- Luz natural y sensor de movimiento

Version

- ajustable
- tieso

Technical details

| | |
|--|--|
| País de la Fabricación |  Alemania |
| fabricante | Byok |
| diseñador | Kai Byok |
| protección | IP20 |
| Volumen de suministro | LED |
| entrada de tensión | 230 - 240 Volt |
| material | aluminio |
| Alimentación (máx. Watt) | 60 Watt |
| LED | incluyendo |
| Indice de reproduccion cromatica | 80 |
| Temperatura de color en grados Kelvin | 3.000 blanco cálido |
| Flujo total luminoso en lm | 4400 lm abajo, de 4400 lm arriba |
| distribución de la luz | directa e indirectamente |
| Dimensions | H 48 cm B 7 cm L 180 cm |

Descripción

The Byok Assiale L is attached directly to the ceiling. It is available as fixed and rotatable. The joint of the rotating lamp is both flexible and robust. A spring-loaded mechanism protects the joint when the lamp is rotated.

The light is offered in anodized aluminum as well as on request powdered in RAL colours. The lamp is offered in three versions: on site DALI dimmable or controllable with light and motion sensors. It emits up- and downlight. In contrast to the Assiale T, this lamp has an L-shape.