




Mawa

Wittenberg 4.0 ceiling lamp 2-lights LED

Oberfläche

- cromo
- negro
- blanco

Technical details

País de la Fabricación	 Alemania
fabricante	Mawa
diseñador	Jan Dinnebier
diseñador 2	mawa engineering
protección	IP20
Volumen de suministro	LED
entrada de tensión	230 - 240 Volt
material	aluminio, metal
angulo del rayo	38 grados
Atenuación	dimnable con control de fase inversa y con reguladores de control de fase
LED	incluyendo
Indice de reproduccion cromatica	95
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
cabeza del alumbrado masa	8 cm
reemplazo de la bombilla:	en el sitio mismo
El rendimiento del sistema	2 x 12,7 Watt
Flujo total luminoso en lm	2.200
distribución de la luz	directamente
Dimensions	K-Merz GmbH & Co. KG Schmalenweg 9 Hambau / Öko-Zentrum NRW / Halle 4 59073 Hamm

Descripción

The Mawa Wittenberg 4.0 ceiling lamp 2-lights LED has two spotlight lamp heads, which are independently adjustable. Each lamp head can be swivelled 90 degrees and rotated 365 degrees. The light emission surface of this lamp is particularly large and well glare-free. With this compact, rectangular lamp design, neither screws nor cables are visible. The Wittenberg 4.0 ceiling lamp 2-lights LED is available in powder-coated white matt or black matt and chrome glossy surfaces. On request, the lamp is also offered with a black ceiling housing and lamp heads in chrome, brass or copper.

The integrated LEDs each have a colour temperature of 2,700 Kelvin extra warm white and can be dimmed on site with a leading or trailing edge phase dimmer. On request they are also available with 3,000 Kelvin warm white or 4,000 Kelvin white. In addition, the lamp is also on request on offer as DALI, Bluetooth or 1-10 volt dimmable versions. The Wittenberg 4.0 ceiling lamp 2-lights LED is also on request available with a colour rendering index of Ra 98, which is closer to natural light (Ra 100).

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.