




Mawa

Wittenberg 4.0 ceiling lamp oval 2-lights LED

Oberfläche

- cromo
- negro
- blanco

Technical details

País de la Fabricación	 Alemania
fabricante	Mawa
diseñador	Jan Dinnebier
diseñador 2	mawa engineering
protección	IP20
Volumen de suministro	LED
entrada de tensión	230 - 240 Volt
material	aluminio, metal
angulo del rayo	38 grados
Atenuación	dimnable con control de fase inversa y con reguladores de control de fase incluyendo
LED	
Indice de reproduccion cromatica	95
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
cabeza del alumbrado masa	8 cm
reemplazo de la bombilla:	en el sitio mismo
El rendimiento del sistema	2 x 12,7 Watt
Flujo total luminoso en lm	2.200
distribución de la luz	directamente
Dimensions	K-Metal GmbH & Co. KG Schwanenweg 9 Hambau / Öko-Zentrum NRW / Halle 4 59073 Hamm

Descripción

The Mawa Wittenberg 4.0 ceiling lamp oval 2-lights LED has two individually adjustable spotlight heads. These two lamp heads can be individually swivelled by 90 degrees and rotated by 365 degrees. Each head has a large and particularly well glare-free light emission surface. With the compact design of the oval ceiling housing, neither screws nor cables are visible.

The Mawa Wittenberg 4.0 ceiling lamp oval 2-lights LED is available in the surfaces powder-coated white matt or black matt and chrome glossy. The integrated LEDs have a standard colour temperature of 2,700 Kelvin extra warm white, on request they are also supplied with 3,000 Kelvin warm white or 4,000 Kelvin white. The light can be dimmed on site with a leading or trailing edge phase dimmer. On request it is also available with DALI dimmable.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees under the item Order Review in the field Order Comment.