

Mawa


Bullauge 6 wall mounting

Durchmesser in cm

- 45
- 60
- 80
- 120



Technical details

País de la Fabricación	 Alemania
fabricante	Mawa
diseñador	Martin Wallroth
protección	IP20
Volumen de suministro	LED
entrada de tensión	230 - 240 Volt
material	aluminio, vidrio acrílico
Atenuación	dimnable con control de fase inversa y con reguladores de control de fase
LED	incluyendo
distribución de la luz	directamente
Dimensions	H 10 cm

Descripción

The Mawa Bullauge 6 wall mounting is installed directly on the wall or ceiling. The lamp is available in four sizes: with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. The housing is made of aluminum and is powder-coated white matt. The opaque, satin diffuser made of plexiglass and the evenly distributed LEDs provide a diffuse and very homogeneous lighting surface. The patented closure of the wall and ceiling lamp allows easy mounting.

The Bullauge 6 is dimmable on site with a leading edge or trailing edge phase dimmer. DALI, 1-10 Volt or push dimmable versions are also available on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white. Other diameters up to 120 cm or other RAL colours are also offered on request. In addition to this lamp for direct wall or ceiling mounting, a lamp with wall or ceiling distance mounting is also available.