




# Mawa

## Bullauge 6 pendant mounting with uplight

### Durchmesser in cm

- 45
- 60
- 80
- 120

### Technical details

<b>País de la Fabricación</b>	 Alemania
<b>fabricante</b>	Mawa
<b>diseñador</b>	Martin Wallroth
<b>protección</b>	IP20
<b>Volumen de suministro</b>	LED
<b>entrada de tensión</b>	230 - 240 Volt
<b>material</b>	aluminio, vidrio acrílico
<b>longitud del cable</b>	250 cm
<b>ajuste de altura</b>	altura determinada
<b>Atenuación</b>	dimnable con control de fase inversa y con reguladores de control de fase
<b>LED</b>	incluyendo
<b>distribución de la luz</b>	directa e indirectamente
<b>Dimensions</b>	H 10 cm

### Descripción

The Mawa Bullauge 6 pendant mounting with uplight emits light both upwards and downwards. The pendant light is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, the lamp is made of aluminum in powder-coated white matt. On request it can also be supplied in other RAL colours. The even distribution of the LEDs and the opaque, satinised plexiglass diffuser ensure a very homogeneous, luminous surface at the bottom of the lamp. The three smaller versions of Bullauge 6 pendant mounting with uplight are suspended on three parallel cables, the largest lamp on four parallel cables. The cables have a maximum length of 250 cm and can be shortened if necessary. On request, the lamp is also available with other cable lengths or without uplight.

The Bullauge 6 can be dimmed with a leading edge or trailing edge phase dimmer. On request, it is also available DALI dimmable. It is also offered with a different diameter up to 120 cm on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.