




Knapstein

AURA-L

Oberfläche

- níquel
- negro

Technical details

| | |
|--|--|
| País de la Fabricación |  Alemania |
| fabricante | Knapstein |
| diseñador | Knapstein |
| protección | IP20 |
| Volumen de suministro | LED |
| entrada de tensión | 230 - 240 Volt |
| Proyección en cm | 50 |
| material | aluminio, metal |
| Atenuación | control por movimientos |
| LED | incluyendo |
| Indice de reproduccion cromatica | >90 |
| Temperatura de color en grados Kelvin | 2.700 extra blanco cálido |
| Dimensiones del soporte de la lámpara | 28 cm |
| El rendimiento del sistema | 1 x 43 Watt + 1 x 10,8 Watt |
| Flujo total luminoso en lm | 6.300 |
| Dimensiones | H 184 cm |

Descripción

The Knapstein AURA-L emits its light upwards as a ceiling floodlight. The lamp has a rotating and swivelling reading arm. The lamp head on the reading arm can be swivelled independently of the reading arm. The Uplight of the ceiling floodlight and the light of the lamp head can be switched and dimmed separately by gesture control.

The sensor area for the ceiling floodlight is located in the centre of the light rod, for the reading arm in the lower area of the plexiglass cover at the bottom of the lamp head. The respective light source is switched on or off with a wiping hand movement in the sensor area. To dim the individual light source continuously, the hand is held at or below the sensor for a longer period of time. Using the memory function, the last set light intensity is saved and automatically selected the next time it is switched on. In the event of a mains failure, the light is automatically switched on if it was previously on. It remains switched off if it was also switched off prior to the power failure. This function is suitable for use with switchable sockets.

The AURA-L from Knapstein is available in black and matt nickel-plated surfaces. The floor lamp is also offered without reading arm.