



# Catellani & Smith

## Syphaduepassi Set 1

### Höhe in cm

- 45
- 75

### Technical details

<b>País de la Fabricación</b>	 Italia
<b>fabricante</b>	Catellani & Smith
<b>diseñador</b>	Enzo Catellani
<b>año</b>	2018
<b>protección</b>	IP44
<b>Volumen de suministro</b>	LED
<b>entrada de tensión</b>	230 - 240 Volt
<b>material</b>	latón, vidrio
<b>base/portalámparas</b>	G4
<b>Potencia en vatios</b>	1 W
<b>LED</b>	incluyendo
<b>Indice de reproduccion cromatica</b>	80
<b>El flujo luminoso en lm</b>	75
<b>Temperatura de color en grados Kelvin</b>	2.700 extra blanco cálido
<b>reemplazo de la bombilla:</b>	en el sitio mismo

### Descripción

The Catellani & Smith Syphaduepassi Set 1 consists of a complete, ready-to-connect outdoor floor lamp with all the necessary accessories. The set includes: a ground spike, a driver required for operation, an extension cable with a length of 500 cm. The connection cable for the power connection must be provided by the customer. The Syphaduepassi luminaire has a glass lens through which the light is focussed and emitted without glare. The bendable light rod made of untreated brass can be realigned as required. With its ground spike, the light can be fixed up to 25 cm into the ground. The Syphaduepassi Set 1 is available with a light with a height of 45 cm or 75 cm (height without spike).

The Syphaduepassi light rod is dustproof with an IP65 protection rating and protected against strong water jets from any angle. The outdoor floor lamp itself is protected against splashing water on all sides and solid foreign bodies with a diameter of 1 mm or more with an IP44 protection rating. The driver and extension cable are protected against temporary submersion with an IP67 protection rating. Syphaduepassi also offers other sets consisting of several complete, ready-to-connect lights.