



Gera Leuchten

Pendant Lamp 10x40 V2x1200


Oberfläche

- aluminio
- acero Inoxidable
- negro-marrón
- negro

Farbtemperatur in Kelvin

- 2.700 extra blanco cálido
- 4.000 blanco

Technical details

| | |
|----------------------------------|--|
| País de la Fabricación |  Alemania |
| fabricante | Gera Leuchten |
| protección | IP20 |
| Volumen de suministro | LED |
| entrada de tensión | 230 - 240 Volt |
| material | aluminio |
| ajuste de altura | altura determinada |
| Atenuación | sensor dimmer |
| Potencia en vatios | 44 W |
| LED | incluyendo |
| El flujo luminoso en lm | 3.360 |
| reemplazo de la bombilla: | en el sitio mismo |
| altura total | 20 - 250 cm |
| Dimensions | H 4 cm B 1 cm L 120 cm |

Descripción

The pendant lamp 10x40 V2x1200 by the German manufacturer Gera is operated with an integrated LED. This LED pendant lamp is available in the finishes aluminium-coloured, stainless steel-coloured and black. The pendant lamp made of aluminium is 120 cm long, 4 cm high and only 1 cm wide. Two opposing light outlets upwards and downwards double your brightness and expand the effect on the room. This elongated pendant lamp made of aluminium has a 58 cm long, 3.4 cm wide and 3.4 cm high ceiling suspension. The lamp connection is located directly on the connection terminal. The lamp is optionally available with a colour temperature of 2,700 Kelvin extra warm white and 4,000 Kelvin white. The LED pendant lamp with upright profile cross-section emits its light brightly and glare-free upwards and downwards. The LED low-voltage technology used in this lamp allows for "cable-free" suspension from fine, current-conducting steel cables. The Gera Leuchten pendant lamp 10x40 V2x1200 is adjustable in total height from 20 cm to 250 cm. This LED pendant lamp can be switched and dimmed touch-free via an integrated sensor dimmer. If required, the integrated LED can be changed by the user himself. The Gera Leuchten pendant lamp 10x40 V2x1200 is also available in other lengths and as a version that can be switched and dimmed by remote control.