




# Bover

## Skybell Plus S/1L

### Dimmbarkeit

- 0-10V regulable
- Regulable en el sitio con control de fase inversa

### Technical details

<b>País de la Fabricación</b>	 España
<b>fabricante</b>	Bover
<b>diseñador</b>	Estudi Manel Molina
<b>año</b>	2019
<b>protección</b>	IP20
<b>Volumen de suministro</b>	LED
<b>entrada de tensión</b>	110 - 240 Volt
<b>material</b>	aluminio, plancha
<b>superficie</b>	negro
<b>angulo del rayo</b>	36 grados
<b>ajuste de altura</b>	altura determinada
<b>Potencia en vatios</b>	4,2 W
<b>LED</b>	incluyendo
<b>Indice de reproduccion cromatica</b>	93
<b>El flujo luminoso en lm</b>	500
<b>Temperatura de color en grados Kelvin</b>	2.700 extra blanco cálido
<b>Dimensiones del dosel</b>	14 cm
<b>Diamètre de l'ombre</b>	6 cm
<b>reemplazo de la bombilla:</b>	en el fabricante / en la fabrica
<b>altura total</b>	200 cm

### Descripción

The lamp shade of the Bover Skybell Plus S/1L pendant lamp has a diameter of 6 cm. The suspension of the lamp can be shortened if necessary. Its total height is 200 cm. The Skybell Plus S/1L has a black lamp shade. The pendant lamp is operated with an integrated LED that has a colour temperature of 2,700 Kelvin extra warm white. The Skybell Plus S/1L can be dimmed on site with a trailing edge phase dimmer or 0-10 volt. The integrated LED is characterised by very good colour rendering with a high colour rendering index of Ra 93. Natural light has a colour rendering index of Ra 100, i.e. the light from this integrated LED is very similar to natural light.