



## LDM

### Kyno Spot Uno Surface-mounted Round

#### Oberfläche

- aluminio mate
- aluminio pulido
- negro
- bronce
- blanco


#### Elemente

- oro
- cromo
- negro
- blanco
- aluminio pulido

#### Dimmbarkeit

- DALI regulable
- Regulable en el sitio con control de fase inversa
- con módulo Casambi

## Technical details

|  |  |
|--|--|
| <b>País de la Fabricación</b>                |  Alemania |
| <b>fabricante</b>                            | LDM  |
| <b>protección</b>                            | IP20   |
| <b>Volumen de suministro</b>                 | LED  |
| <b>entrada de tensión</b>                    | 230 - 240 Volt   |
| <b>material</b>                              | aluminio   |
| <b>angulo del rayo</b>                       | 20 - 60 grados   |
| <b>Potencia en vatios</b>                    | 12 W   |
| <b>LED</b>                                   | incluyendo   |
| <b>Indice de reproduccion cromatica</b>      | 97   |
| <b>El flujo luminoso en lm</b>               | 1.252  |
| <b>Temperatura de color en grados Kelvin</b> | 2.700 extra blanco cálido  |
| <b>Dimensiones del dosel</b>                 | 10 cm  |
| <b>cabeza del alumbrado masa</b>             | Longitud 18 cm, 4 cm   |
| <b>reemplazo de la bombilla:</b>             | en el fabricante / en la fabrica   |

## Descripción

The LDM Kyno Spot Uno Surface-mounted Round is a surface-mounted ceiling spot made of aluminum. The light is focused by a frosted, optical glass lens. The beam angle of the light can be continuously adjusted between 20 and 60 degrees by turning the glass lens out of or into the lamp head. With a larger beam angle, the light is distributed over a larger area.

The Kyno Spot Uno Surface-mounted Round is available in the surfaces aluminum polished, aluminum matt, bronze, white and black matt. The ring-shaped design element on the lamp head is available in aluminum polished, matt chrome-plated, matt gold-plated, white matt and black matt. The swivel joint has the same surface as the design element, only the lamp with the element in aluminum polished has a chrome-plated swivel joint. The lamp head is a total of 18 cm long without unscrewing the lens and has a diameter of 4 cm.

The Kyno surface-mounted ceiling spotlight is offered with three dimming options: on site dimmable with a trailing edge phase dimmer, DALI dimmable or with an integrated Casambi module. The Kyno Spot Uno Surface-mounted Round is supplied with a colour temperature of 2,700 Kelvin extra warm white. On request, the spotlight is also available with 3,000 Kelvin warm white, 4,000 Kelvin white or with dim-to-warm technology. With the dim-to-warm function, the light colour of the LED changes to a warmer tone when dimmed (from 3,000 Kelvin warm white to 1,800 Kelvin extra warm white). The lamp is operated with Full Spectrum LEDs whose light resembles sunlight.