




Byok

Squadra Mono 165

Oberfläche

- aluminium poli
- Matt aluminium
- Aluminium noir
- satin poudre blanche enduite

Technical details

| | |
|--|---|
| Pays de fabrication |  Allemagne |
| fabricant | Byok |
| concepteur | Kai Byok |
| protection | IP20 |
| Contenu de la livraison | LED |
| aptitude de tension | 230 - 240 Volt |
| matériel | aluminium |
| longueur de câble | 250 cm |
| réglage de la hauteur | hauteur déterminée |
| atténuation | dimmerable sur place avec commande gradateur de phase inverse |
| LED | y compris |
| Indice de rendu des couleurs | 90 |
| La température de couleur en Kelvin | 2.700 extra blanc chaud |
| Les performances du système | 10 x 3,6 Watt |
| Flux lumineux total en LM | 3.060 |
| répartition de la lumière | directement |
| Dimensions | H 4 cm B 9 cm L 165 cm |

Description

The Byok Squadra Mono 165 is a pendant lamp characterised by its clear alignment. The Squadra Mono 165 is the big sister of the Squadra Mono 125. Consisting of only one element, a simple and attractive design is created. The hollow profile used gets its effect through the mounting hooks installed to one side. The filigree steel ropes underline the purist optics.

The profile endings come with matt transparent and translucent end caps. Thus the Byok Squadra Mono 165 sets additional highlights when switched on. The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The LEDs are placed in sockets enabling you to singly exchange the illuminants. This lamp is available in four surfaces.