



Cini & Nils

Passepartout 25


Version

- or
- chrome
- noir
- blanc

Dimmbarkeit

- capteur gradateur
- dimmable sur place avec commande gradateur de phase inverse
- avec module Casambi

Technical details

| | |
|--|--|
| Pays de fabrication |  Italie |
| fabricant | Cini & Nils |
| concepteur | Luta Bettonica |
| année | 2017 |
| protection | IP20 |
| Contenu de la livraison | LED |
| aptitude de tension | 230 - 240 Volt |
| Diamètre en cm | 25 |
| matériel | acier, aluminium |
| réglage de la hauteur | hauteur déterminée |
| LED | y compris |
| Indice de rendu des couleurs | 92 |
| La température de couleur en Kelvin | 2.800 blanc chaud |
| canopée Dimensions | 16 cm |
| Les performances du système | 1 x 9 Watt Downlight + 2 x 5 Watt Uplight |
| Flux lumineux total en LM | 2.200 |
| hauteur totale | 250 cm |
| Dimensions | H 2 cm Ø 25 cm |

Description

The Cini & Nils Passepartout 25 pendant lamp emits light simultaneously upwards and downwards. The light is bundled in both directions by a lens. The lamp has a diameter of 25 cm and a height of 2.3 cm. The Passepartout 25 is available in four versions: white matt, black matt, chrome polished and gold polished. All versions except gold have a diamond-polished aluminum support element for the lens. The gold version has a matt brass support. The lamp itself is always made of steel.

The Passepartout 25 is offered in three dimmabilities: dimmable on site with a trailing edge phase dimmer, with an integrated Casambi module or with an integrated sensor dimmer. The version with Casambi module can be dimmed with the Casambi App via Bluetooth by a smartphone / tablet. The version with sensor dimmer is switched on and off by moving the hand under the sensor. The light is dimmed by holding the hand under the sensor. The total height is a maximum of 250 cm, the cables can be shortened if required. On request, an accessory is available with which two Passepartout lamps can be mounted on a common power connection.