




## Cini & Nils

### Convivio pendant lamp LED

#### Oberfläche

- chrome
- noir

#### Technical details

|  |  |
|--|--|
| <b>Pays de fabrication</b>                 |  Italie |
| <b>fabricant</b>                           | Cini & Nils  |
| <b>concepteur</b>                          | Luta Bettonica   |
| <b>concepteur 2</b>                        | Mario Melocchi   |
| <b>année</b>                               | 2005   |
| <b>protection</b>                          | IP20   |
| <b>Contenu de la livraison</b>             | LED  |
| <b>aptitude de tension</b>                 | 230 - 240 Volt   |
| <b>Diamètre en cm</b>                      | 11   |
| <b>matériel</b>                            | acier, aluminium, laiton, verre  |
| <b>longueur de câble</b>                   | 385 cm   |
| <b>réglage de la hauteur</b>               | hauteur déterminée   |
| <b>atténuation</b>                         | dimmerable sur place avec commande gradateur de phase inverse                              |
| <b>Puissance en Watt</b>                   | 13 W   |
| <b>LED</b>                                 | y compris  |
| <b>Indice de rendu des couleurs</b>        | 92   |
| <b>Flux lumineux en lm</b>                 | 1.300  |
| <b>La température de couleur en Kelvin</b> | 2.800 blanc chaud  |
| <b>canopée Dimensions</b>                  | 14 cm  |
| <b>Dimensions</b>                          | H 65 cm   Ø 11 cm  |

#### Description

The Cini & Nils Convivio pendant lamp LED has a transparent glass lens, which bundles the light and emits it directly downwards. The lamp is available in chrome and matt black. An LED with a colour temperature of 2,800 Kelvin warm white is integrated as the light source. The light can be dimmed on site with a trailing edge phase dimmer. On request, it is also offered with a Casambi module. With the optional available Casambi module, the light can be dimmed with the Casambi App via Bluetooth using a smartphone / tablet. The maximum cable length of 385 cm can be individually set during assembly.