




Mawa

Wittenberg 4.0 Druff table lamp LED

Oberfläche

- noir
- beige
- bleu
- gris
- rouge
- blanc

Technical details

Pays de fabrication	 Allemagne
fabricant	Mawa
concepteur	Jan Dinnebieer
concepteur 2	Martin Wallroth
protection	IP20
Contenu de la livraison	LED
aptitude de tension	230 - 240 Volt
matériel	aluminium, métal
angle du faisceau	38 degrees
couleur de câble	gris
longueur de câble	250 cm
atténuation	intégrée Pushbutton gradateur
LED	y compris
Indice de rendu des couleurs	95
La température de couleur en Kelvin	2.700 extra blanc chaud
tête de luminaire masse	8 cm
remplacement des ampoules :	sur le site meme
Les performances du système	2 x 12,7 Watt
Flux lumineux total en LM	2.200
répartition de la lumière	directement
Dimensions	H 9 cm B 10 cm L 20 cm

Description

The Mawa Wittenberg 4.0 Druff table lamp LED has two individually adjustable spotlight heads. Each lamp head can be individually rotated by 365 degrees and swivelled by 90 degrees. The lamp heads are both half-flush mounted in the lamp housing. The lamp is dimmed continuously by a push button dimmer on the housing. A memory function saves the last light intensity setting and automatically selects it again when the lamp is switched on again.

The Wittenberg 4.0 Druff table lamp LED is available in powder-coated matt black, beige, grey, blue, red or matt white. On request it is also available with a black housing and lamp heads in copper or completely in other RAL colours. As standard, the lamp is supplied with a colour temperature of 2,700 Kelvin extra warm white. On request it is also available with 3,000 Kelvin warm white or 4,000 Kelvin white. The colour rendering index of the lamp is Ra 92, but on request it is also offered with Ra 98, which is closer to natural light (Ra 100). The scope of delivery includes a honeycomb grid with which the light can be emitted without glare.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.