Mawa

Bullauge 6 wall distance mounting

Durchmesser in cm

- 45
- 60
- 80
- 120

Technical details

Pays de fabrication	🇩🇪 Allemagne
fabricant	Mawa
concepteur	Martin Wallroth
surface	weiß matt / white matt
protection	IP20
Contenu de la livraison	LED
aptitude de tension	230 - 240 Volt
matériel	verre acrylique, aluminium
atténuation	gradable avec variateur à coupure de phase et à commande de phase
LED	y compris
répartition de la lumière	directement
hauteur totale	15 cm
Dimensions	H 10 cm

Description

The Mawa Bullauge 6 wall distance mounting is a wall or ceiling lamp. It has a distance of 5 cm to the wall or ceiling thanks to the supplied spacer. This gives it a total height of 15 cm in all sizes. On request, the lamp is also available with a different distance. The lamp is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, it has an aluminum housing in powder-coated white matt. Due to the even arrangement of the LEDs and the opaque, satinized diffuser made of plexiglass, the lamp has a diffuse and very homogeneous lighting surface. The wall and ceiling lamp can be easily installed with its patented closure.

The Bullauge 6 wall distance installation can be regulated with a leading edge or trailing edge phase dimmer. On request the light is also available DALI, 1-10 Volt or Push dimmable. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white. In addition, the wall and ceiling light is offered on request with a different diameter up to 120 cm, in other RAL colours or with uplight. Furthermore the lamp is also available for direct wall or ceiling mounting.