



# Cini & Nils

## Acqua with double canopy


### Oberfläche

- or
- argent
- blanc

### Version

- Downlight
- Uplight

## Technical details

<b>Pays de fabrication</b>	 Italie
<b>fabricant</b>	Cini & Nils
<b>concepteur</b>	Luta Bettonica
<b>année</b>	2014
<b>protection</b>	IP20
<b>Contenu de la livraison</b>	LED
<b>aptitude de tension</b>	230 - 240 Volt
<b>matériel</b>	acier, aluminium
<b>réglage de la hauteur</b>	hauteur déterminée
<b>atténuation</b>	avec gradateur integre commande par un interrupteur
<b>LED</b>	y compris
<b>Indice de rendu des couleurs</b>	95
<b>La température de couleur en Kelvin</b>	2.800 blanc chaud
<b>canopée Dimensions</b>	Longueur 33 cm, largeur 11 cm, hauteur 5 cm
<b>Les performances du système</b>	5 x 5,6 Watt
<b>Flux lumineux total en LM</b>	3.250
<b>hauteur totale</b>	200 cm
<b>Dimensions</b>	H 86 cm

## Description

This Cini & Nils Acqua consists of two multiple lamps suspended next to each other on a canopy. A total of five lighting elements are integrated. The lamp is available in the surfaces white, silver matt and gold matt. On request it is also offered in silver leaf or gold leaf. The oval canopy is supplied in the matching surface to the lamp. The Acqua is offered in two versions: As an uplight it emits indirect light directed upwards and as a downlight it emits direct light directed downwards.

The pendant light with multiple canopy is operated with a switch-controlled, integrated dimmer, with which the light can be dimmed continuously via the normal light switch. No additional cables are required for this. The dimming function is activated by switching on and off once. The maximum light intensity is reached within seven seconds. To set the desired light intensity, switch on and off again. The set light intensity is saved via a memory function and automatically selected again when the light is switched on again. On request, the Acqua with double canopy is also available on site dimmable with Push.

This light has a total of five individual Acqua elements. On request, the pendant lamp is also available with up to ten elements. The pendant light has a maximum height of 200 cm, the cables can be shortened if required. A decentralisation kit is offered as an accessory, which allows the lamp to be installed independently of the power supply.