

Cini & Nils

Acqua with double canopy

Oberfläche

- or
- argent
- blanc

Version

- Downlight
- Uplight

Technical details

Pays de fabrication

fabricant

concepteur

année

protection

Contenu de la livraison

aptitude de tension

matériel

réglage de la hauteur

atténuation

LED

Indice de rendu des

couleurs

La température de couleur

en Kelvin

canopée Dimensions

Les performances du

système

Flux lumineux total en LM

hauteur totale Dimensions Italie

Cini & Nils

Luta Bettonica

2014

IP20

LED

230 - 240 Volt acier, aluminium

hauteur déterminée

avec gradateur integre commande par un interrupteur

uninterrupte

y compris

95

2.800 blanc chaud

Longueur 33 cm, largeur 11 cm,

hauteur 5 cm

5 x 5,6 Watt

3.250

200 cm

H 86 cm

Description

This Cini & Nils Acqua consists of two multiple lamps suspended next to each other on a canopy. A total of five lighting elements are integrated. The lamp is available in the surfaces white, silver matt and gold matt. On request it is also offered in silver leaf or gold leaf. The oval canopy is supplied in the matching surface to the lamp. The Acqua is offered in two versions: As an uplight it emits indirect light directed upwards and as a downlight it emits direct light directed downwards.

The pendant light with multiple canopy is operated with a switch-controlled, integrated dimmer, with which the light can be dimmed continuously via the normal light switch. No additional cables are required for this. The dimming function is activated by switching on and off once. The maximum light intensity is reached within seven seconds. To set the desired light intensity, switch on and off again. The set light intensity is saved via a memory function and automatically selected again when the light is switched on again. On request, the Acqua with double canopy is also available on site dimmable with Push.

This light has a total of five individual Acqua elements. On request, the pendant lamp is also available with up to ten elements. The pendant light has a maximum height of 200 cm, the cables can be shortened if required. A decentralisation kit is offered as an accessory, which allows the lamp to be installed independently of the power supply.