




## IP44.DE

### Piek 100 brown, direct plug, 3000 Kelvin

#### Technical details

|  |   |
|--|---|
| <b>Pays de fabrication</b>                 |  Chine |
| <b>fabricant</b>                           | IP44.DE   |
| <b>concepteur</b>                          | Sebastian David Büscher   |
| <b>année</b>                               | 2020  |
| <b>protection</b>                          | IP65  |
| <b>Contenu de la livraison</b>             | LED   |
| <b>aptitude de tension</b>                 | 230 - 240 Volt  |
| <b>matériel</b>                            | acier Inoxydable, aluminium, verre  |
| <b>surface</b>                             | brun  |
| <b>longueur de câble</b>                   | 500 cm  |
| <b>atténuation</b>                         | gradable avec variateur à coupure de phase et à commande de phase                         |
| <b>Puissance en Watt</b>                   | 6 W   |
| <b>LED</b>                                 | y compris   |
| <b>Flux lumineux en lm</b>                 | 310   |
| <b>La température de couleur en Kelvin</b> | 3.000 blanc chaud   |
| <b>Diamètre de l'ombre</b>                 | 6 cm  |
| <b>longueur de la tige lampes</b>          | 100 cm  |
| <b>remplacement des ampoules :</b>         | chez le fabricant / a l'usine   |
| <b>Dimensions</b>                          | H 106 cm  |

#### Description

The IP44.de Piek 100 is an outdoor floor lamp with ground spike, which allows it to be repositioned at a new location again and again. This lamp has a total height of 106 cm and its lamp rod a length of 100 cm. Its lamp head can be tilted by 180 degrees. With its IP65 protection rating, this outdoor floor lamp is both dustproof and protected against water jets from any angle. The Piek 100 is operated with a high-efficiency Power LED which can be dimmed on site with a trailing edge phase dimmer. The spotlight-shaped lamp head is made of powder-coated cast aluminum, the lamp rod made of powder-coated stainless steel.

The Piek offered here is in brown and has a colour temperature of 3,000 Kelvin warm white. It is supplied with a protective contact plug and is connected directly to the mains.