



# less'n'more Zeus Wall Light Z-BWL2

#### Dimmbarkeit

- Variateur tactile sur le support mural
- dimmerable sur place avec commande gradateur de phase inverse

#### Oberfläche

- aluminium
- noir
- blanc

#### flexible\_arm

- vert Textile
- rouge Textile
- marron Textile
- blanc Textile
- noir Textile
- bleu textile
- anthracite Textile
- aluminium

## Description

The Less'n'more Zeus Wall Light Z-BWL2 is a surface-mounted lamp for the wall. It is also suitable for mounting on a flush-mounted box. Its wall mounting / mounting plate is made of aluminum and has a diameter of 10 cm. When mounting, the wall mounting can be freely mounted by 360 degrees. The wall lamp has a flexible lamp arm that can be stretched and bent as desired. At maximum extension of the arm, the lamp has a height of 61 cm. The flexible arm is available in the following colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

Lamp head and wall bracket are offered in the surfaces aluminum and black. The beam angle of the light can be adjusted continuously between 15 and 75 degrees by turning the glass lens out of or into the lamp head. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated as illuminant.

The Zeus Wall Light Z-BWL2 is available dimmable on site with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The version with push button dimmer can be switched and dimmed via the push button. The flexible lamp arm is offered in special colours on request. This Zeus wall lamp is also available on request with a supply cable and safety plug for direct connection to a power supply. In addition to this lamp, Less'n'more also offers the smaller Zeus Wall Light Z-BWL1 with a maximum height of 30 cm.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@1001lights.com

### **Technical details**

Pays de fabrication	💻 All
fabricant	less'n'
concepteur	less'n'
protection	IP43
Contenu de la livraison	LED
aptitude de tension	230 - 2
matériel	alumir
angle du faisceau	15 - 75
Puissance en Watt	4,2 W
LED	y com
Indice de rendu des couleurs	90
Flux lumineux en lm	450
La température de couleur en Kelvin	2.700
tête de luminaire masse	3 cm
remplacement des ampoules :	sur le s
Support mural Dimensions	10 cr
Dimensions	H max

Allemagne less'n'more less'n'more lP43 LED 230 - 240 Volt aluminium, verre 15 - 75 degres 4,2 W y compris 90 450 2.700 extra blanc chaud 3 cm sur le site meme 10 cm H max. 61 cm

www.1001lights.com