



Mawa

Wittenberg 4.0 ceiling lamp head-flush LED


Oberfläche

- noir
- blanc

Farbtemperatur in Kelvin

- 2.700 extra blanc chaud
- 3.000 blanc chaud
- 4.000 blanc

Technical details

Pays de fabrication	 Allemagne
fabricant	Mawa
concepteur	Jan Dinnebier
concepteur 2	mawa engineering
année	2021
protection	IP20
Contenu de la livraison	LED
aptitude de tension	230 - 240 Volt
matériel	aluminium, métal
angle du faisceau	38 degrees
atténuation	gradable avec variateur à coupure de phase et à commande de phase
Puissance en Watt	12,7 W
LED	y compris
Indice de rendu des couleurs	95
tête de luminaire masse	8 cm
remplacement des ampoules :	sur le site meme
Dimensions	H 10 cm B 12 cm L 12 cm

Description

The Mawa Wittenberg 4.0 ceiling lamp head-flush LED has an adjustable spotlight lamp head. This lamp head is integrated completely flush in the rectangular ceiling housing, i.e. it disappears completely into the ceiling housing when folded in. It can be rotated by 365 degrees and swivelled by 90 degrees. The large light-emitting surface of the spotlight head is well glare-reduced. The compact design of the lamp means that neither screws nor cables are visible. This ceiling lamp is available with a powder-coated matt white (RAL 9016) or matt black finish (RAL 9005).

The integrated LED is offered with a colour temperature of 2,700 Kelvin extra warm white, 3,000 Kelvin warm white or 4,000 Kelvin white. On request, it is also available with dim-to-warm technology. With the dim-to-warm function, the light colour of the LED changes to a warmer tone when dimmed (from 3,100 Kelvin warm white to 1,850 Kelvin extra warm white). The Wittenberg 4.0 ceiling light head-flush LED can be dimmed on site with a trailing edge or leading edge phase dimmer; on request, it is also available as a DALI dimmable version or a version that can be dimmed by smartphone via Bluetooth.

The spotlight has a beam angle of 38 degrees. The beam angle determines the angle at which the light emerges from an LED spotlight. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the Order comments field.