

LDM

Kyno Spot Uno Surface-mounted Round

Oberfläche

- Matt aluminium
- · aluminium poli
- noir
- bronze
- blanc

Elemente

- · aluminium poli
- blanc
- chrome
- noir
- or

Dimmbarkeit

- dimmable DALI
- dimmerable sur place avec commande gradateur de phase inverse
- avec module Casambi

Description

The LDM Kyno Spot Uno Surface-mounted Round is a surface-mounted ceiling spot made of aluminum. The light is focused by a frosted, optical glass lens. The beam angle of the light can be continuously adjusted between 20 and 60 degrees by turning the glass lens out of or into the lamp head. With a larger beam angle, the light is distributed over a larger area.

The Kyno Spot Uno Surface-mounted Round is available in the surfaces aluminum polished, aluminum matt, bronze, white and black matt. The ringshaped design element on the lamp head is available in aluminum polished, matt chrome-plated, matt gold-plated, white matt and black matt. The swivel joint has the same surface as the design element, only the lamp with the element in aluminum polished has a chrome-plated swivel joint. The lamp head is a total of 18 cm long without unscrewing the lens and has a diameter of 4 cm.

The Kyno surface-mounted ceiling spotlight is offered with three dimming options: on site dimmable with a trailing edge phase dimmer, DALI dimmable or with an integrated Casambi module. The Kyno Spot Uno Surface-mounted Round is supplied with a colour temperature of 2,700 Kelvin extra warm white. On request, the spotlight is also available with 3,000 Kelvin warm white, 4,000 Kelvin white or with dim-to-warm technology. With the dim-to-warm function, the light colour of the LED changes to a warmer tone when dimmed (from 3,000 Kelvin warm white to 1,800 Kelvin extra warm white). The lamp is operated with Full Spectrum LEDs whose light resembles sunlight.

Technical details

Pays de fabrication fabricant protection Contenu de la livraison aptitude de tension matériel angle du faisceau Puissance en Watt

canopée Dimensions tête de luminaire masse

remplacement des ampoules :

LED y compris Indice de rendu des couleurs 97 Flux lumineux en lm 1.252 La température de couleur en Kelvin 2.700 extra blanc chaud

10 cm Longueur 18 cm, 4 cm chez le fabricant / a l'usine

Allemagne

230 - 240 Volt

20 - 60 degres

aluminium

LDM

IP20

LED

12 W