

Byok

Piani Mono 165 Downlight



Oberfläche

- Gepolijst aluminium
- mat aluminium
- matzwart

Leuchte

- hoogte verstelbaar
- hoogte verstelbaar

Technical details

Land van fabricage	 Duitsland
fabrikant	Byok
ontwerper	Kai Byok
bescherming	IP20
Omvang van de levering	LED
voltage geschiktheid	230 - 240 Volt
materiaal	aluminium
kabellengte	300 cm
dimmen	dimbaar op locatie met faseafsnijding dimmer
LED	inclusief
Kleurweergave-index	>90
Kleurtemperatuur in Kelvin	2.700 extra warm wit
bulb vervangen:	bij de fabrikant / fabriek
prestaties van het systeem	10 x 3,6 Watt
Totale lichtstroom in lm	3.060
Dimensions	H 1 cm B 5 cm L 165 cm

Omschrijving

The Byok Piani Mono 165 Downlight is a pendant lamp. The lamp body of the Piani Mono 165 Downlight is milled out of massive aluminum and polished or eloxated by hand afterwards. Ten LEDs are dazzle-free installed due to reflector technics and they may be exchanged singly.

Three surfaces are on offer: aluminum matt, aluminum polished or black matt. This pendant lamp is offered height-determinable (the cables can be set to the desired length during assembly) or height-adjustable (the total height can also be adjusted after assembly). The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.