



# Serien Lighting

## Cavity Recessed L

### Oberfläche

- aluminium
- zwart
- bronzen
- wit

### Voltage

- 230 - 240
- 110 - 125

## Technical details

|                                   |   |
|-----------------------------------|---|
| <b>Land van fabricage</b>         |  Duitsland |
| <b>fabrikant</b>                  | Serien Lighting   |
| <b>ontwerper</b>                  | Jean-Marc da Costa und Manfred Wolf   |
| <b>jaar</b>                       | 2019  |
| <b>bescherming</b>                | IP20  |
| <b>Omvang van de levering</b>     | LED   |
| <b>voltage geschiktheid</b>       | 110 - 240 Volt  |
| <b>Diameter in cm</b>             | 13  |
| <b>materiaal</b>                  | aluminium   |
| <b>dimmen</b>                     | dimbaar met fase- en fase-afsnijding en fase-regelingsdimmer                                  |
| <b>Wattage</b>                    | 20 W  |
| <b>LED</b>                        | inclusief   |
| <b>Kleurweergave-index</b>        | >95   |
| <b>Lichtstroom in lm</b>          | 2.070   |
| <b>Kleurtemperatuur in Kelvin</b> | 2.700 extra warm wit  |
| <b>bulb vervangen:</b>            | ter plaatse zelf  |
| <b>Dimensions</b>                 | H 3 cm   Ø 13 cm  |

## Omschrijving

The Serien Lighting Cavity Recessed L is suitable for installation in cavity ceilings. This ceiling lamp is 2.8 cm high and has a diameter of 12.5 cm. It emits its light mainly directly downwards. The LED is recessed in the lamp so that the light is shielded to the side. Part of the emitted light is reflected by the lamp itself. The Cavity Recessed L is made of aluminum and is available in black, white, aluminum gloss finish and bronze finish. The integrated LED can be replaced if necessary and is dimmable on site with a trailing edge or leading edge phase dimmer. It is supplied with a colour temperature of 2,700 Kelvin extra warm white as standard. On request, the recessed ceiling light is also available with a colour temperature of 3,000 Kelvin warm white or DALI dimmable. A driver is included in the scope of delivery.