



## **Technical details**

Land van fabricage	Italië
fabrikant	Catellani & Smith
ontwerper	Enzo Catellani
jaar	2018
bescherming	IP44
Omvang van de levering	LED
voltage geschiktheid	230 - 240 Volt
materiaal	glas, messing
base/versie	G4
LED	inclusief
Kleurweergave-index	80
Kleurtemperatuur in Kelvin	2.700 extra warm wit
bulb vervangen:	ter plaatse zelf
prestaties van het systeem	2 x 1 Watt
Totale lichtstroom in lm	150
Dimensions	H 45 + 75 cm

## Catellani & Smith Syphaduepassi Set 2

## Omschrijving

The Catellani & Smith Syphaduepassi Set 2 consists of two complete outdoor floor lamps, ready for connection, with all necessary accessories. The two Syphaduepassi lamps can be easily connected together using the Quick Connectors system. Only a single power connection is required for installation. All necessary plug connections are included. The set contains:

- One lamp with a height of 45 cm
- one lamp with a height of 75 cm
- an extension cable with a length of 500 cm
- a driver necessary for lamp operation

Each Syphaduepassi lamp can be fixed with its ground spike up to 25 cm into the ground. The heights of the lamps (45 cm and 75 cm) are indicated without ground spike. The lamps each have a glass lens through which the light emitted is focused and glare-free. The lamp rod made of untreated brass of each lamp can be bent and can be realigned if necessary. With IP44 protection, the Syphaduepassi lamps are protected against splashing water on all sides and solid foreign bodies with a diameter of 1 mm or more. With IP65 protection, their lamp rods are dust-tight and protected against strong jets of water from any angle. Drivers and extension cables are protected against temporary immersion with IP67 protection. From Syphaduepassi, also a set of one complete lamp and sets of three, four, five or nine complete lamps are offered.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@1001lights.com

www.1001lights.com