



less'n'more

Athene Wall Light A-BWL2

Dimmbaarheid

- Touch Dimmer op de wandhouder
- dimbaar op locatie met faseafsnijding dimmer

Oberfläche

- aluminium
- zwart
- wit

flexible_arm

- textiel wit
- textiel zwart
- textiel blau
- textiel antraciet
- aluminium
- textile groen
- textiel rood
- textiel bruine

Technical details

Land van fabricage	 Duitsland
fabrikant	less'n'more
ontwerper	less'n'more
bescherming	IP43
Omvang van de levering	LED
voltage geschiktheid	230 - 240 Volt
materiaal	aluminium, glas
stralingshoek	25 - 100 Graad
Wattage	4,8 W
LED	inclusief
Kleurweergave-index	90
Lichtstroom in lm	600
Kleurtemperatuur in Kelvin	2.700 extra warm wit
lampkop massa	7 cm
bulb vervangen:	ter plaatse zelf
Wall mount Afmetingen	10 cm
Dimensions	H max. 63 cm

Omschrijving

The Less'n'more Athene Wall Light A-BWL2 is mounted on the wall as standard. It is also suitable for mounting on a flush-mounted box. Its mounting plate or wall bracket has a diameter of 10 cm and can be freely mounted 360 degrees during installation. This Athene wall lamp has a flexible lamp arm that can be stretched and bent as desired. With a maximum extension of the lamp arm, the lamp has a height of 63 cm. The flexible arm is available in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

The lamp head and wall bracket are offered in the surfaces aluminum and black. By turning the glass lens out of or into the lamp head, the beam angle of the light can be continuously adjusted between 25 and 100 degrees. With a larger beam angle, the light is distributed over a larger area. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated as the light source.

The Athene Wall Light A-BWL2 is available on site dimmable with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The version with push button dimmer can be switched and dimmed via the push button. The flexible lamp arm is offered in additional special colours on request. In addition, the lamp is also available on request with a supply cable and safety plug for direct connection to a power supply.