

less'n'more

Ylux Wall / Ceiling Spotlight



Leuchtenkopf

- polerowane aluminium
- biały mat
- lśniąca biel
- czarny matowy
- błyszczący czarny


Baldachin

- beton biały
- szary beton

Dimmbarkeit

- ściemniacz obrotowy na głowie
- ściemniaczna kontroli faz przyciemniania

Technical details

Kraj produkcji	 Niemcy
producent	less'n'more
projektant	less'n'more
ochrona	IP43
zakres dostawy	LED
napięcie przydatność	230 - 240 Volt
tworzywo	aluminium, beton, szkło
kąt nachylenia belki	50 - 100 stopni
Moc w watach	12,6 W
LED	Łącznie
Wskaźnik oddawania barw	95
Strumień świetlny w lm	1.200
baldachim Wymiary	15 cm
Głowica lampy Wymiary	9 cm
wymiana żarówek:	na miejscu
Ilość LED	1
dystrybucja światła	bezpośrednio
Dimensions	H 18 cm

Opis

The Less'n'more Ylux Wall / Ceiling Spotlight can be used for the ceiling or wall. The lamp head can be rotated by 360 degrees and tilted by 135 degrees. It has a diameter of 9 cm. The light source is an integrated LED with a colour temperature of 2,700 Kelvin extra warm white. The beam angle of the lamp head is continuously adjustable from 50 to 100 degrees by turning the glass lens out of or back into the lamp head. With a larger beam angle, the light is distributed over a larger area.

The Ylux Wall / Ceiling Spotlight has a canopy with a diameter of 15 cm and a height of 5.5 cm. This is available in concrete white or concrete grey. On request, the lamp is also offered with a canopy in black. Due to the natural composition of the material, the surfaces for the canopy can vary, i.e. lighter/darker. On request, this wall / ceiling lamp is also available as a recessed lamp with an aluminum mounting plate with a diameter of 10 cm.

The lamp head of the Ylux wall / ceiling spotlight is available in the colours aluminum polished, glossy white, matt white, glossy black or matt black. It is made of aluminum. The lamp is offered dimmable on site with a trailing edge phase dimmer or with an integrated rotary dimmer on the lamp head. On request, the wall and ceiling lamp is also available DALI dimmable.