



Lichtlauf

Lichtenfest 80


Oberfläche

- miedź
- złoto
- srebro
- biały

Dimmbarkeit

- DALI ściemniania
- ściemniająca kontrola faz przyciemniania

Technical details

Kraj produkcji	 Niemcy
producent	Lichtlauf
projektant	Christoph Matthias
rok	2005
ochrona	IP20
zakres dostawy	LED
napięcie przydatność	230 - 240 Volt
Średnica w cm	80
tworzywo	aluminium
kolor przewodu	przezroczysty
długość kabla	250 cm
regulacja wysokości	wysokość ustalona
LED	łącznie
Wskaźnik oddawania barw	90
Temperatura barwowa w stopniach Kelvina	3.000 biała ciepła
wydajność systemu	2 x 12 Watt
Dimensions	Ø 80 cm

Opis

The Lichtlauf Lichtenfest 80 consists of three layers of leaf-metallised metal formed into a volume. The Lichtenfest by the German manufacturer Lichtlauf emits light downwards and between the three layers of the lampshade, which is formed into a volume, also reflected into the room. Between the three layers of the lampshade, an intensive glow is created by multiple reflection. Each Lichtlauf Lichtenfest lamp is individually handmade and unique. Due to the handcrafted manufacturing process, there may be irregularities in the leaf-finished surface. The two integrated LEDs, each with an output of 12 watts, have a colour temperature of 3,000 Kelvin warm white. The light of the LEDs of this dimmable lamp is characterised by a very good colour rendering with a high colour rendering index of Ra 90. The Lichtlauf Lichtenfest is available in the surfaces copper and white matt. This pendant lamp is suspended from the ceiling canopy by a thin wire cable. The height is adjusted directly on the ceiling canopy. The transparent 250 cm long cable, which serves as a supply line, can be shortened if necessary. This LED pendant lamp is available as an on-site dimmable version with a phase cut-off dimmer or DALI dimmable version. The lampshade of the Lichtenfest 80 has a diameter of approx. 80 cm. The Lichtenfest is also available in other sizes. Special sizes are possible for all Lichtenfest lamps, also special colours and other cable lengths are available on request. On request, the surface can also be covered with real gold, platinum or moon gold. Prices on request.