




B.Lux

Lite Hole C/W 120

Oberfläche

- miedź
- czarny
- złoto
- biały

Technical details

Kraj produkcji	 Hiszpania
producent	B.Lux
projektant	David Abad
ochrona	IP20
zakres dostawy	LED
napięcie przydatność	230 - 240 Volt
Średnica w cm	120
tworzywo	aluminium, Szkło akrylowe
ściemnianie	Naciśnij ściemniania
LED	łącznie
Wskaźnik oddawania barw	>90
Temperatura barwowa w stopniach Kelvina	3.000 biała ciepła
wydajność systemu	1 x 19,5 Watt + 1 x 41 Watt
Całkowity strumień świetlny w lm	11.624
Dimensions	H 8 cm Ø 120 cm

Opis

The B.Lux Lite Hole C/W 120 ceiling light consists of two concentric aluminum rings that sit on top of each other. Its lamp body has a diameter of 120 cm and a height of 6 cm. Including the ceiling bracket, this lamp is 8 cm high. Thanks to a diffuser made of opal white acrylic glass, any glare is prevented and the light is homogeneously distributed downwards.

The Lite Hole C/W 120 is available in the surfaces white matt, black matt, copper and gold. The two integrated LEDs each have a colour temperature of 3,000 Kelvin warm white. One of the two LEDs has an output of 19.5 watts, the other 41 watts. The ceiling light can be dimmed with Push or DALI. Push requires a 4-wire mains supply line for dimming, DALI a 5-wire. A version that can be dimmed with a Casambi module by smartphone via Bluetooth is also available on request. The version with Casambi module can be operated easily and intuitively via mobile devices with the free CASAMBI app (iOS and Android). Casambi thus expands the control options with functions such as dimming, grouping of lamps, programming of groups and scenes, automations and much more. In addition to this ceiling light, the Lite Hole is also offered with a diameter of 60 cm or 90 cm.